













# The **AGRICOLD** Series


AGRICOLD 302 / AGRICOLD 302 YF

## CHARACTERISTICS

AGRICOLD 302	AGRICOLD 302 YF
--------------	-----------------

SCG302R	SCG302H
---------	---------






	TYPE OF REFRIGERANT		
	AUTOMATIC WORKING CYCLE No manual taps	•	•
	HIGH PRECISION RECOVERY FUNCTION	•	•
	AUTOMATIC OIL INJECTION refillable/hermetic bottles ( <b>OIL LOCK</b> )	•	•
	AUTOMATIC DYE INJECTION refillable/hermetic bottles ( <b>OIL LOCK</b> )	✓	✓
	HEATER BELT INCLUDED	•	•
	USB PORT	•	•
	INTERNAL DATA BASE including commercial and agricultural vehicles	•	•
	INTEGRATED AUTOMATIC NITROGEN AND FORMING GAS LEAK CHECK ( <b>CFU-NITRO</b> / <b>CFU-NITRO.HD.XX</b> )	✓	✓
	INTERNAL FLUSHING	•	•
	READY TO USE ON HYBRID OR ELECTRIC CARS with rapid oil decontamination system	•	•
	A/C SYSTEM PROFESSIONAL FLUSHING ( <b>ACC-FLUSHING</b> )	✓	✓
	A/C SYSTEM DIAGNOSYS	•	•
	CONFIGURABLE GAS TYPE from HF01234YF to --> R134a	•	•
	BLUETOOTH CONNECTION APP OKSY®GEN+	•	•



• STANDARD ✓ OPTION



## ACCESSORIES

CODE	DESCRIPTION	AGRICOLD 302	AGRICOLD 302 YF
 ACC-88.072	Gas bottle adapter 1/4	✓	
 ACC-88.011	Straight adapter HP 1/4	✓	
 ACC-88-289H	Universal bottle adapter HF01234YF		✓
 O-PK00051 O-PK00051 OPZ	Printer kit	✓	✓
 OAC0002-KIT	12 V Power supply	✓	✓



# RANGE

R134a



HF01234YF



AGRI

Heavy Duty

MODEL	FAST 342	FAST 322	FAST 302	ECOS 302	FAST 342 YF	FAST 322 YF	FAST 302 YF	ECOS 302 YF	AGRICOLD 302	AGRICOLD 302 YF	HD 202
-------	----------	----------	----------	----------	-------------	-------------	-------------	-------------	--------------	-----------------	--------

## TECHNICAL FEATURES

Process	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic	Fully Automatic
Display	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 128x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel	Graphic LCD 264x64 Pixel
Full Recovery Function	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Tank Capacity	18 Kg	18 Kg	12 Kg	9 Kg	12 Kg	12 Kg	12 Kg	9 Kg	12 Kg	12 Kg	40 Kg
Heater Belt	YES	YES	YES	YES	YES	YES	YES	YES	SI YES	YES	YES
Scale Accuracy	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g	+/- 5 g
Automatic Oil Injection	YES 1 Scale	YES 1 Scale	YES 1 Scale	YES	YES 1 Scale	YES 1 Scale	YES 1 Scale	YES	YES	YES	YES 1 Scale
Automatic Dye Injection	YES 1 Scale	YES 1 Scale	Option	Option	YES 1 Scale	YES 1 Scale	Option	Option	Option	Option	YES 1 Scale
Printer	YES	YES	Option	Option	YES	YES	Option	Option	Option	Option	Option
Compressor	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	10 cc	20 cc
Vacuum Pump	100 l/min	100 l/min	70 l/min	50 l/min	100 L/min	100 L/min	70 L/min	50 L/min	100 L/min	100 L/min	200 L/min Doppio Stadio
Air Purge	Automatic High Precision	Automatic	Automatic	Automatic	Automatic High Precision	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Stauts Indicators	YES	YES	NO	NO	YES	YES	NO	NO	NO	NO	NO
Data Base	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
A/C Diagnostic / AC Pressure Test	YES	YES	AC Pressure Test Only	AC Pressure Test Only	YES	YES	AC Pressure Test Only	AC Pressure Test Only	AC Pressure Test Only	AC Pressure Test Only	AC Pressure Test Only
Hybrid Function	YES Rapid oil decontamination	YES Rapid oil decontamination	YES	YES	YES Rapid oil decontamination	YES Rapid oil decontamination	YES	YES	Option (Rapid)	Option (Rapid)	YES Rapid oil decontamination
Nitrogen Leak Check	Automatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Automatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic	Option/Semiautomatic
Refrigerant HF01234YF Identifier	NO	NO	NO	NO	Opzione	Opzione	Opzione	NO	NO	NO	NO
A/C Flushing Kit	Option	Option	Option	NO	Option	Option	Option	NO	Option	Option	Option
Bluetooth Connection	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	NO
Remote Control / Interface	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	YES via Bluetooth	NO
Charging Gear Pump	NO	NO	NO	NO	NO	NO	NO	NO	NO	NO	Option
12 V Power Supply	NO	NO	NO	NO	NO	NO	NO	NO	Option	Option	NO
Power Supply	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz	220V 50 Hz 12V DC	220V 50 Hz 12V DC	220V 50 Hz
Dimensions	58x55x120 cm	58x55x120 cm	51x48x94 cm	51x48x94 cm	58x55x120 cm	58x55x120 cm	54x58x99 cm	52x56x99 cm	55x63x86 cm	48x68x88 cm	55x60x120 cm
Weight	67/76 Kg	65/74 Kg	61/70 Kg	55/64 Kg	65/74 Kg	65/74 Kg	61/70 Kg	57/66 Kg	62/71 Kg	62/71 Kg	117/126 Kg
Packaging dimensions	63x63x123 cm	63x63x123 cm	63x63x123 cm	54x58x116 cm	63x63x123 cm	63x63x123 cm	63x63x123 cm	54x58x116 cm	68x57x100 cm	68x57x100 cm	80x60x145 cm

## SCOPE OF DELIVERY

Hp LP Quick Couplers	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included
Hoses	3m	3m	3m	3m	3m	3m	3m	3m	7,5 m	7,5 m	3 m
Blanket	YES	YES	Option	Option	YES	YES	Option	Option	NO	NO	NO
Power Cord	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Calibration Handle	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Extra oil bottle	YES	YES	YES	YES	YES	YES	YES	YES	Option	Option	YES
2 x temperature probes	Included	Included	NO	NO	Included	Included	NO	NO	NO	NO	NO